Attorney Docket No: 0505-0704P

Appl. No. 09/680,429

Page 2

2. (Amended) The piezo-film speaker according to claim 1, wherein said flat piezo-film includes the characteristics of a radius (R) of curvature at each curved portion in a range of 210mm ≤R ≤360 mm.

Sul i

3. (Amended) The piezo-film speaker according to claim 1, wherein said flat piezo-film includes an area S of a principal surface of said piezo-film in a range of $40 \text{ cm}^2 \leq S \leq 100 \text{ cm}^2$.

4. (Amended) The piezo-film speaker according to claim 1, wherein said flat piezo-film includes:

a radius (R) of curvature at each curved portion in a range of 210mm \leq R \leq 360 mm and an area (S) of a principal surface of said piezo-film is in a range of 40 cm² \leq S \leq 100 cm².

- 5. The piezo-film speaker according to claim 2, wherein said piezo-film speaker has a film thickness (t) of 110 μ m.
- 6. The piezo-film speaker according to claim 3, wherein said piezo-film speaker has a film thickness (t) of 28 μ m.



7. (Amended) A motorcycle helmet including a hard, thin helmet shell, said helmet comprising:

Attorney Docket No: 0505-0704P

Appl. No. 09/680,429

Page 3

a piezo-film speaker built into said helmet, wherein said piezo-film speaker includes a flat piezo-film curvedly supported to form at least one curved portion, said flat piezo-film having at least a radius (R) of curvature at each curved portion in a range of R \geq 200 mm or an area (S) of a principal surface of said piezo-film is in a range of S \geq 40 cm².

8. The motorcycle helmet according to claim 7, wherein said flat piezo-film has a radius (R) of curvature at each curved portion in a range of 210mm \leq R \leq 360 mm and an area S of a principal surface of said piezo-film in a range of 40 cm² \leq S \leq 100 cm².

9. (Amended) The motorcycle belimet according to claim 7, wherein said flat piezo-film has a radius (R) of curvature at each curved portion in a range of 210mm ≤R ≤360 mm.

10. (Amended) The motorcycle helmet according to claim 7, wherein said flat piezo-film has an area S of a principal surface of said piezo-film in a range of $40 \text{ cm}^2 \leq \text{S} \leq 100 \text{ cm}^2$.

- 11. (Amended) The motorcycle helmet according to claim 8, wherein said piezo-film speaker has a film thickness (t) of 110 μ m.
- 12. (Amended) The motorcycle helmet according to claim 9, wherein said piezo-film speaker has a film thickness (t) of 28 μ m.

A2 02

A3

Attorney Docket No: 0505-0704P

Appl. No. 09/680,429

Page 4

13. (Amended) The motorcycle helmet according to claim 7, wherein said helmet further comprises:

a head liner fixed on an inner surface of said helmet shell;

a head inner removably and dividedly mounted so as to cover the head liner; and

ear inners and a chin inner removably and dividely mounted with respective liners on the inner surface of said helmet shell.

14. (Amended) The motorcycle helmet according to claim 13, wherein said helmet further comprises a plurality of said flat piezo-film speakers, each speaker mounted directly to said inner surface of said helmet shell.

Please add the following claims:

--15. The piezo-film speaker according to claim 1, wherein said radius (R) of curvature at each curved portion is in a range of $210 \le R \le 340$ mm and an area S of a principal surface of said piezo-film in a range of $50 \text{ cm}^2 \le S \le 100 \text{ cm}^2$.

16. The piezo-film speaker according to claim 7, wherein said radius (R) of curvature at each curved portion is in a range of $210 \le R \le 340$ mm and an area S of a principal surface of said piezo-film in a range of $50 \text{ cm}^2 \le S \le 100 \text{ cm}^2$.--

A3